

AS1104N



Ciclo positivo / Positive cycle (90' +90°C > +3°C)
11 Kg
Ciclo negativo / Negative cycle (240' +90°C > -18°C)
6 Kg
Capacità massima teglie Max. trays capacity
3x 60x40cm GN1/1 =65(h) mm

AS1105N



Ciclo positivo / Positive cycle (90' +90°C > +3°C)
18 Kg
Ciclo negativo / Negative cycle (240' +90°C > -18°C)
9 Kg
Capacità massima teglie Max. trays capacity
5x 60x40cm GN1/1 =65(h) mm

	AS1104N	AS1105N
	+90°C / +3°C +90°C / -18°C	+90°C / +3°C +90°C / -18°C
	820 x 700/1470 x 800(h) mm	820 x 700/1470 x 900(h) mm
	700 x 587 x 275(h) mm	700 x 587 x 375(h) mm
	113 L	154 L
	+32°C / 55%HR	+38°C / 55%HR
	ventilata / ventilated	ventilata / ventilated
DEFROST	manuale / manual	manuale / manual
GAS	R452a	R452a
	automatica / automatic	automatica / automatic
	elettronico / electronic	elettronico / electronic
CONTROL		
	60 mm	60 mm
	841 W	875 W
	230V / 50Hz	230V / 50Hz
MATERIAL	acciaio Inox AISI 304 stainless steel AISI 304	acciaio Inox AISI 304 stainless steel AISI 304
REVERSIBLE	no	no
	no	no
STANDARD	3 supporti teglie 3 trays supports	5 supporti teglie 5 trays supports
	130 Kg	130 Kg
	140 Kg	140 Kg
	850 x 730 x 1113(h) mm	850 x 730 x 1113(h) mm

Professional Line

Abbattitori / Blast chillers /
Cellules de refroidissement rapide / Schnellkühler