

AS1110N



Ciclo positivo / Positive cycle (90' +90°C > +3°C)
36 Kg
Ciclo negativo / Negtive cycle (240' +90°C > -18°C)
18 Kg
Capacità massima teglie Max. trays capacity
10x 60x40cm GN1/1 =65(h) mm

AS1114N



Ciclo positivo / Positive cycle (90' +90°C > +3°C)
50 Kg
Ciclo negativo / Negtive cycle (240' +90°C > -18°C)
26 Kg
Capacità massima teglie Max. trays capacity
14x 60x40cm GN1/1 =65(h) mm

	AS1110N	AS1114N
	+90°C / +3°C +90°C / -18°C	+90°C / +3°C +90°C / -18°C
	820 x 800/1570 x 1750(h) mm	820 x 800/1570 x 1950(h) mm
	700 x 687 x 990(h) mm	700 x 687 x 1090(h) mm
	250 L	320 L
	+38°C / 55%HR	+38°C / 55%HR
	ventilata / ventilated	ventilata / ventilated
DEFROST	manuale / manual	manuale / manual
GAS	R452a	R452a
	automatica / automatic	automatica / automatic
	elettronico / electronic	elettronico / electronic
CONTROL	60 mm	60 mm
	2100 W	2400 W
	400V / 50Hz	400V / 50Hz
1 Ph		
MATERIAL	acciaio Inox AISI 304 stainless steel AISI 304	acciaio Inox AISI 304 stainless steel AISI 304
	no	no
REVERSIBLE		
	no	no
STANDARD	10 supporti teglie 10 trays supports	14 supporti teglie 14 trays supports
	190 Kg	200 Kg
	200 Kg	210 Kg
	850 x 850 x 1913(h) mm	850 x 830 x 2013(h) mm

Professional Line

Abbattitori / Blast chillers
Cellulles de refroidissement rapide / Schnellkühler