

G-AB1203



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
12 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
8 Kg
Capacità massima teglie Max. trays capacity
3 x 60 x 40cm GN1/1 = 65(h) mm

G-AB1805



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
18 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
14 Kg
Capacità massima teglie Max. trays capacity
5 x 60 x 40cm GN1/1 = 65(h) mm

i	G-AB1203	G-AB1805
	+90°C / +3°C +90°C / -18°C	+90°C / +3°C +90°C / -18°C
	800 x 815 x 945(h) mm	800 x 815 x 1015(h) mm
	660 x 400 x 330(h) mm	660 x 400 x 400(h) mm
	140 L	169 L
	+43°C / 60%HR	+43°C / 60%HR
	ventilata / ventilated	ventilata / ventilated
DEFROST	gas caldo / hot gas	gas caldo / hot gas
GAS	R290	R290
	automatica / automatic	automatica / automatic
	elettronico / electronic	elettronico / electronic
CONTROL	70 mm	70 mm
	700 W	720 W
	230V / 50Hz	230V / 50Hz
MATERIAL	acciaio Inox AISI 304 stainless steel AISI 304	acciaio Inox AISI 304 stainless steel AISI 304
REVERSIBLE	si / yes	si / yes
	no	no
STANDARD	3 supporti teglie 3 trays supports	5 supporti teglie 5 trays supports
	104 Kg	116 Kg
	140 Kg	159 Kg
	900 x 870 x 1140(h) mm	870 x 900 x 1210(h) mm

Professional Line

Abbattitori / Blast chillers
Cellules de refroidissement rapide / Schnellkühler