

G-T3



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
8 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
5 Kg
Capacità massima teglie Max. trays capacity
3-GN2/3 = 65(h) mm

G-D5A



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
18 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
14 Kg
Capacità massima teglie Max. trays capacity
5 x 60 x 40cm GN1/1 = 65(h) mm

i	G-T3	G-D5A
	+70°C / +3°C +70°C / -18°C	+90°C / +3°C +90°C / -18°C
	600 x 585 x 390(h) mm	800 x 815 x 1015(h) mm
	360 x 330 x 200(h) mm	660 x 400 x 400(h) mm
	33 L	169 L
	+32°C / 60%HR	+43°C / 60%HR
	ventilata / ventilated	ventilata / ventilated
DEFROST	manuale / manual	manuale / manual
GAS	R290	R290
	manuale / manual	manuale / manual
	elettronico / electronic	elettronico / electronic
	60 mm	60 mm
	500 W	720 W
	230V / 50Hz	230V / 50Hz
MATERIAL	acciaio Inox AISI 304 stainless steel AISI 304	acciaio Inox AISI 304 stainless steel AISI 304
REVERSIBLE	no	no
	no	no
STANDARD	3 supporti teglie 3 trays supports	5 supporti teglie 5 trays supports
	42 Kg	116 Kg
	52 Kg	159 Kg
	720 x 740 x 570(h) mm	870 x 900 x 1210(h) mm

Professional Line

Abbattitori / Blast chillers
Cellules de refroidissement rapide / Schnellkühler