

G-AB4010



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
40 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
28 Kg
Capacità massima teglie Max. trays capacity
10 x 60 x 40cm GN1/1 = 65(h) mm

AB5514



Ciclo positivo / Positive cycle (90' +70°C > +3°C)
50 Kg
Ciclo negativo / Negative cycle (240' +70°C > -18°C)
38 Kg
Capacità massima teglie Max. trays capacity
15 x 60 x 40cm GN1/1 = 65(h) mm

	G-AB4010	AB5514
	+90°C / +3°C +90°C / -18°C	+90°C / +3°C +90°C / -18°C
	800 x 815 x 1645(h) mm	800 x 815 x 2170(h) mm
	660 x 400 x 870(h) mm	660 x 400 x 1170(h) mm
	241 L	319 L
	+43°C / 60%HR	+43°C / 60%HR
	ventilata / ventilated	ventilata / ventilated
DEFROST	gas caldo / hot gas	gas caldo / hot gas
GAS	R290	R404a / R290
	automatica / automatic	automatica / automatic
	elettronico / electronic	elettronico / electronic
CONTROL		
	70 mm	70 mm
	900 W	2500 W
	230V / 50Hz	400V / 50Hz
MATERIAL	acciaio Inox AISI 304 stainless steel AISI 304	acciaio Inox AISI 304 stainless steel AISI 304
	si / yes	si / yes
	no	no
STANDARD	10 supporti teglie 10 trays supports	14 supporti teglie 15 trays supports
	150 Kg	210 Kg
	200 Kg	236 Kg
	870 x 900 x 1840(h) mm	870 x 900 x 2380(h) mm

Professional Line

Abbattitori / Blast chillers
Cellules de refroidissement rapide / Schnellkühler