

AFV 350

- Linea arrotondata priva di spigoli e facile da pulire.
- Perno di scorrimento, cromato rettificato e lappato.
- Boccole di scorrimento autolubrificante.
- Paracolpo su carrello in gomma vulcanizzata.
- Coperchio supporto vela smontabile.
- Apertura vela trasversale 30 mm.
- Parafetta rimovibile in acciaio inox con incastro rapido a baionetta.
- Tutte le minuterie acciaio inox.
- Copertura inferiore con accesso diretto ai componenti elettrici.
- Scheda elettromeccanica commutabile 110-220-380 V monofase e trifase.
- Affilatoio con vaschetta inferiore di protezione.
- Sistema di tenuta stagna su puleggia.
- 48 mm di distanza fra la lama e il corpo macchina.
- Estrattore lama di serie.
- Braccio stringisalumi con staffa chiodata inox rimovibile per la pulizia.




- *Rounded design, no sharp edges and easy to clean*
- *Chrome plated, ground slide and lapped rod*
- *Self lubricating slide rod bushings*
- *Vulcanized rubber stops on carriage*
- *Removable support cover for thickness gauge plate*
- *Slicing thickness 30 mm.*
- *Removable stainless steel slice deflector with bayonet fitting*
- *Stainless steel screws and fittings*
- *Bottom cover with electronic component direct access*
- *Changeover electronic circuit 110-220-380 V single and three phase.*
- *Built in sharpening tool with bottom protection*
- *Enclosed and sealed belt pulley*
- *48 mm distance between blade and motor*
- *Standard blade removable tool*
- *Salami arm with removable food pusher for easy cleaning*



Sblocco braccio stringisalumi
Parma ham fixing arm



Ampio spazio tra lama e motore
Wide space from blade to motor



							A	B	C	D	E	F	G	L	X	Y	H	W			
	mm/inch.	1ph - 3ph	watt/hp	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kg	mm	Kg
AFV 350	350/14"	1ph - 3ph	370/0,50	29	310	300x270	468	338	660	600	530	750	715	630	270	255	255	255	38	870x840x750	53